

# Eaton 5E900UF

Catalog Number: 5E900UF

Eaton 5E Gen2 UPS USB FR, 900 VA, 480 W, Input: French, Outputs: (2) French, Tower

## General specifications

|                      |                     |
|----------------------|---------------------|
| Product Name         | Catalog Number      |
| Eaton 5E Gen2 UPS    | 5E900UF             |
| Product Length/Depth | Product Height      |
| 288 mm               | 148 mm              |
| Product Width        | Product Weight      |
| 100 mm               | 5.27 kg             |
| Warranty             | Compliances         |
| 2 year               | CB                  |
|                      | LVD Directive       |
|                      | EMC Directive       |
|                      | RoHS Directive      |
|                      | Packaging Directive |
|                      | WEEE Directive      |
|                      | Batteries Directive |
| Certifications       |                     |
| IEC/EN 62040-1       |                     |
| IEC/EN 62040-2       |                     |
| CE                   |                     |
| Cm                   |                     |
| IEC/EN 62040-3       |                     |
| EAC                  |                     |
| UKCA                 |                     |
| Ukr                  |                     |

## Technické údaje produktu

## Zdroje

### Secondary frequency - max

60 Hz

### Wattage

480 W

### Form factor

Tower

### Includes network card

No

### Input connection

Protective contact (SCHUKO)

### Input voltage - min

140 V

### Output voltage - max

257 V

### Secondary frequency - min

50 Hz

### Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

### Battery type

Sealed, lead-acid

### Efficiency

95

### Number of output connections French standard (Type E)

2

### Special features

Automatic Voltage Regulation (AVR)

Saves space with a compact tower design

HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)

Includes two French Outlets

### Construction type

Free standing model

### Output voltage - min

195 V

### Color

Black

Extended battery capability

No

Output voltage range

195-257 V

Topology

Line-interactive

Surge protection

Yes

Input nominal voltage

230V default (220/230/240V)

Input frequency range

45-63 Hz

Internal bypass

No

Input voltage - max

300 V

Voltage type

AC

Phase (output)

1

Battery management

Automatic battery test, deep-discharge protection, cold-start capable

Auto shutdown function

Yes

Operating temperature - min

0 °C

VA rating

850 VA

Potential free switch contact

No

Receptacle

(2) French

Phase (input)

1

Package contents

Quick start

Safety instructions

Feed type

1

Runtime graph

View runtime graph

User interface

LEDs

Battery quantity

1

Operating temperature - max

40 °C

Voltage

230V

Hot swap power

No

Input cord length

1.5 m

Temperature range

0° to 40°C (32° to 104°F)

Ethernet interface

No

Communication

USB port (HID compliant)

Relative humidity

0-90% non-condensing

Output apparent power

900 VA

Rack mounting kit

No

Output frequency

50/60 Hz

Type of interface

USB

Primary frequency - min

45 Hz

Battery rating

12 V / 9 Ah

Type

UPS

Output nominal voltage

230V

Expansion slots

No

Input voltage range

140-300 V

Nominal frequency

50/60 Hz

Primary frequency - max

63 Hz



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. Všechna  
práva vyhrazena.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)